

Dyna-Blue[®]

Heavy Duty Cable Lubricant



With Clingability



- » Clean - Easy To Use
- » Stays Slippery - Won't Dry Out
- » Low Cost

- » Temperature Stable - No Waste
- » Safe To Use With Most Cables
- » UL Listed

Dyna-Blue® Cable Lubricant

Dyna-Blue® Lubricant is a clean, slow-drying, and easy-to-apply gel lubricant. It is a thick gel with “clingability” for easy handling and application. Dyna-Blue® combines effectiveness with economy. It is a good lubricant for everyday use in general electrical applications.

Dyna-Blue® Lubricant is harmless to humans, environmentally safe, compatible with most common cable jacket materials, and exceptionally easy to work with. pH neutral and non-toxic.

Dyna-Blue® is UL listed.

| Package Size | Dyna-Blue® Product # | Unit/Case |
|---|----------------------|-----------|
| 55-gal drum (208 L) | D-Drum | 1 |
| 5-gal pail (18.9 L) | D-640 | 1 |
| 1-gal pail (3.78 L) 4/case | D-128 | 4 |
| 1-qt squeeze bottle (0.95 L) 12/case | D-35 | 12 |

Characteristics

1. Dyna-Blue® shows excellent lubricity on a variety of cable jacket types. Using PVC conduit, the following COF's were measured:
PVC .11, THHN .09, XHHW .08
Method described in “Coefficient of Friction Measurement on Polywater’s Friction Table, 2007.” Typical values determined using 200 lbs/ft normal force.
2. Dyna-Blue® dries slippery. It leaves little residue and will not cement cables to conduit.
3. Dyna-Blue® does not contain wax, grease or silicone.
4. Dyna-Blue® has a wide temperature use range: 20°F to 120°F (-5°C to 50°C).
5. Dyna-Blue® passes IEEE 1210 physical and electrical testing on a wide variety of cable materials. It does not stress crack polyethylene. Refer to the technical bulletin for details.
6. Dyna-Blue® is stable and will not separate after exposure to high heat or freezing.
7. Dyna-Blue® will not stain sheet rock, carpet, concrete or clothing. Wipe up excess product when necessary.
8. Dyna-Blue® has no flash point and dried residue is non-flammable.

To view technical information on our website go to:

Support Page: www.polywater.com/dynablue.html

Lubricant Application Videos: www.polywater.com/videos.asp



phone: 1-800-328-9384
1-651-430-2270
fax: 1-651-430-3634

email: support@polywater.com

11222 60th Street North, Stillwater, MN 55082, U.S.A.

ADHESIVES | CLEANERS | **LUBRICANTS** | SEALANTS

WWW.POLYWATER.COM

Important Notice: The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from product's use, regardless of the legal theory asserted.